



09.362.72.32.0

BPW replacement brake caliper TS2 4309

BPW replacement brake caliper (pre greased)

incl. guide pins and attachment parts

brake caliper without brake pad 05.362.72.22.0 / 05.362.72.32.0 (type plate)

Item 702 can be retrofitted as an option.

Important installation instruction:

First fit cylinder head screw 325 in the long fixed bearing (mark 1 on the brake caliper) and then cylinder head screw 345 in the short floating bearing (mark 2 on the brake caliper) and tighten at the tightening torque of **260 Nm** (250 - 270 Nm).

Item	Name	BPW code number	Dimension	Quantity
323	Repair kit guide pins TS2 item 325 - 328, 335, 336, 345 - 348, 354, 356, 369, 373	09.801.08.69.0	for one axle side	1
324	Repair kit cylinder head screw + sealing cap TS2 item 325, 335, 345, 369, 373	09.801.08.71.1	for one axle side	1
325	Cylinder head screw	03.340.12.32.0	M 16 x 1,5 x 103 - 10.9 / SW 14	1
326	Guide pin, long (fixed bearing)	05.001.00.70.0	Ø 18 / 26 / 37 x 123	1
328	Guide bush (fixed bearing)	03.112.33.13.0	Ø 37 / 41 x 73	1
335	Sealing cap	03.001.00.44.0	M 49 x 1,5 / SW 14	2
336	Kit O-ring	05.801.47.92.0		1
345	Cylinder head screw	03.340.12.31.0	M 16 x 1,5 x 73 - 10.9 / SW 14	1
346	Guide pin, short (floating bearing) incl. item 355	05.001.00.73.0	Ø 18 / 26 / 37 x 70	1
348	Guide bush (floating bearing)	03.112.33.16.0	Ø 37 / 41 x 34	1
354	Bellow	05.130.08.30.0	Ø 49 x 36	2
355	O-ring	02.5680.08.00	Ø 35 x 2	1
356	Ring Only deliverable per kit 09.801.07.62.0 (item 352) or 09.801.07.87.0 (item 334)! Only deliverable per kit 09.801.07.62.0 (item 352) or 09.801.07.87.0 (item 334)!	03.310.11.20.0	Ø 37 / 48 x 5,4	2



Item	Name	BPW code number	Dimension	Quantity
361	Repair kit bellow item 363	09.801.08.81.0	for one axle	1
363	Bellow	05.130.08.32.0	Ø 40.7 / 75.4 Only deliverable per kit 09.801.08.81.0!	1
369	Assembly kit cap, O-ring TS2 item 370, 371, 373	05.801.47.87.0		1
373	BPW ECO Disc Grease	02.1040.60.00	25 g	1
395	Pad holding bar	03.001.00.64.0	151 x 42 Only deliverable per kit 09.801.08.70.0	1
702	Wear sensor set TS2 for one axle	05.801.48.92.0		1

